



ESPN HD Certification

RF Equipment:

- Andrew 2.4 Meter Antenna
- 4-Port Feed
- 2 MCL 400w Ku-Band HPA's
- 2 Miteq U-9956-6-1K Upconverters
- 1 Standard MT650 Analog Receiver
- Tektronix 1705A Spectrum Monitor

Production Equipment:

- Panasonic AV-HS400A Switcher
- 2 Sony 32" LCD Monitors
- 1 17" Marshall HD/SD LCD Display
- 2 7" Marshall HD/SD LCD Displays
- 1 Videotek VTM-4100-E Test Instrument
- 1 Allen & Heath WZ1442 Audio Mixer
- 1 Shure FP-42 Edit Mixer
- 1 Videotek AMP-210 Stereo Audio Monitor
- 1 Wohler AMP1S8-MDA Audio Monitor
- 1 Wohler AMP2E8-MDA Audio Monitor
- 1 Crown D75A Audio Amps
- 1 Evertz VIP8-HSN Multimage Display
- 7 Evertz 7700DA7-HD DA's
- 3 Evertz 7700DA-SD DA's
- 6 Evertz 7700ADA7-EQ DA's
- 1 Evertz 7736CD2 Dual Comp to SDI
- 8 Evertz 7700DA-AES DA's
- 4 Evertz 7700ADA7-AUD DA's
- 1 Evertz 7720ADC Dual AUD to AES
- 1 Evertz 7750TG SD TSG
- 1 Evertz 7751TG2 HD TSG
- 1 AJA FS1 Multiformat Converter
- 1 Pixelmetrix DVStation

Generator:

- 20 kw Generator
- 80 Hour Fuel Capacity

Physical:

- 2000 Chevrolet Chassis
- Weight: 25,950lbs.
- Length: 29'6"
- Width: 8'
- Height: 13'1" (Antenna Stowed)

Digital Capable:

- Phase Stable Modulators
- Upconvertors Tunable to 125 kHz
- Phase Stable LNB's

Encryption Capabilities:

- Tiernan PGCA Conditional Access
- Tandberg RAS Conditional Access
- BISS 1 & BISS E

Communication Equipment:

- 1 RTS MCE325 2-Channel PL Stations
- 4 RTS BP325 Intercom Beltpacks
- 4 Beyer Dynamic Intercom Headsets
- 1 Telex 4001/4010 IFB Station
- 4 RTS IFB325 Beltpacks
- 2 Gentner Hybrid Telco Coupler
- 1 Gentner Microtel IFB Interface
- 1 Telos Link Intercom Interface
- 3 Telular Cellular Terminals
- 1 3G Aircard WiFi Router
- DSS Receiver

Power Requirements:

- 208-240 Volt, 100 Amp, Single Phase
- 200 Feet Shore Power Cable
- Cam-lock ends & pigtails

Licensing:

- FCC License • Intelsat • New Skies

K19

4415 Wagon Trail Ave
Las Vegas, NV 89118

310-575-4400
800-728-5465
800-SAT-LINK
www.pssiglobal.com